



RED LINE PROFESSIONAL-SERIES 0W20 MOTOR OIL



- Full-synthetic, OEM-certified formula provides excellent low-temperature flow during cold starts
- Helps to prevent low-speed pre-ignition (LSPI) in turbocharged gas direct-injection engines
- Resistant to oxidation to avoid sludge and has low volatility for reduced oil consumption and longer drain intervals
- Developed to protect against turbocharger deposits and protects emission control system catalysts
- Can be used in vehicles powered by ethanol-containing fuels up to E85

APPROVED / CERTIFIED:

API SN Plus with Resource Conserving

ILSAC GF-5

dexos1™ Gen 2

RECOMMENDED FOR:

CHRYSLER
MS-6395

FORD
WSS-M2C947-A
WSS-M2C947-B1

TYPICAL PROPERTIES:

| | |
|---------------------------------|---------|
| API Service Class | SN PLUS |
| SAE Viscosity Grade (Motor Oil) | 0W-20 |
| Vis @ 100°C, cSt | 8.5 |
| Vis @ 40°C, cSt | 45 |
| Viscosity Index | 169 |
| CCS Viscosity, Poise, @ °C | 57@-35 |
| Freezing Point °C | -40 |
| Freezing Point °F | -40 |
| HTHS Vis, cP @150°C, ASTM D4741 | 2.7 |

PACKAGE SIZES:

- 12804 - 0W20 Prof-Series - quart
- 12805 - 0W20 Prof-Series - 5 quart
- 12808 - 0W20 Prof-Series - 55 gallon

ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

- FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks
- Low volatility for reduced oil consumption
- Long-life certification for reduced wear protection following factory drain intervals
- For high- and low-mileage engines
- Compatible with conventional and synthetic oils
- Withstands extreme temperatures

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM