



# RED LINE PROFESSIONAL-SERIES 5W30 MOTOR OIL



Full-synthetic, OEM-certified formula provides excellent low-temperature flow during cold starts  
 Helps to prevent low-speed pre-ignition (LSPI) in turbocharged gas direct-injection engines  
 Resistant to oxidation to avoid sludge and has low volatility for reduced oil consumption and longer drain intervals  
 Developed to protect against turbocharger deposits and protects emission control system catalysts  
 Can be used in vehicles powered by ethanol-containing fuels up to E85

### APPROVED / CERTIFIED:

API SP  
 ILSAC GF-6  
 dexos1™, Gen 2, Gen 3

### RECOMMENDED FOR:

API SN+  
 CHRYSLER  
 MS-6395  
 FORD  
 WSS-M2C946-A  
 WSS-M2C946-B1  
 GM  
 GM4718M  
 GM6094M  
 HONDA/ACURA  
 HTO-06

### TYPICAL PROPERTIES:

API Service Class	SP
SAE Viscosity Grade (Motor Oil)	5W-30
Vis @ 100°C, cSt	10.3
Vis @ 40°C, cSt	61
Viscosity Index	169
CCS Viscosity, Poise, @ °C	59 @-30
Pour Point °C	-40
Pour Point F	-40
HTHS Vis, cP @150°C, ASTM D4741	3.0

### PACKAGE SIZES:

12204 - 5W30 Prof-Series - quart  
 12205 - 5W30 Prof-Series - 5 quart  
 12208 - 5W30 Prof-Series - 55 gallon

## ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks  
 Low volatility for reduced oil consumption  
 Long-life certification for reduced wear protection following factory drain intervals  
 For high and low-mileage engines  
 Compatible with conventional and synthetic oils  
 Withstands extreme temperatures

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM