



RED LINE 0W20 MOTOR OIL



- Recommended for small cars, hybrids, and some trucks like Honda Insight and Civic Hybrids, Toyota Solara, Camry, Rav4, Tundra 5.7L and Venza
- Lightest passenger car motor oil available from Red Line
- Increased fuel economy and improved wear at cold start
- Better flow at extremely cold temperatures compared to 5W20

RECOMMENDED FOR:

ILSAC GF-5
API SN/SM/SL/CF
ACEA A5/B5

GM
dexos1®
88865188
88865189

dexos is a registered trademark
owned by General Motors Corp.

BMW LL-14 FE+

Fiat 500X MS-6395

Honda/Acura
08798-9036
08798-9037
08798-9032

Jaguar/Land Rover
STJLR.51.5122

Mazda
0000-G5-0W20-MQ
0000-77-0W20-QT

Mitsubishi MZ320106

Mopar 68152004PA

Nissan KLAM7-00204

Subaru
SOA15208AA15A
SOA868V9300

Toyota 00279-0WQTE-01

Toyota/Lexus 00289-1QT0W

TYPICAL PROPERTIES:

ACEA Service Class	A5 B5
API Service Class	SN/SM/SL/SG/CF
SAE Viscosity Grade (Motor Oil)	0W20
Vis @ 100°C, cSt	9.1
Vis @ 40°C, cSt	48
Viscosity Index	172
CCS Viscosity, Poise, @ °C	55@-35
Pour Point, °C	-60
Pour Point, °F	-76
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	9
HTHS Vis, cP @150°C, ASTM D4741	2.9

PACKAGE SIZES:

11804 - 0W20 Motor Oil - quart
11805 - 0W20 Motor Oil - 1 gallon

ABOUT RED LINE MOTOR OIL

- Full-synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM