



# RED LINE 0W20 MOTOR OIL



- Designed to reduce Low Speed Pre-Ignition (LSPI)
- Increased fuel economy and improved wear at cold start
- Better flow at extremely cold temperatures compared to 5W20
- Increased fuel economy and improved wear at cold start

## RECOMMENDED FOR:

**API SP/SN+/SN/SM**  
**ACEA C2/C5/C6, A5/B5, A7/B7, A1/B1**  
**BMW LL-14 FE+/LL-17 FE+**  
**Ford M2C-947-A/B1, M2C-948-B, M2C962-A1**

**GM**  
 888651188  
 888651189  
 dexos1<sup>®</sup>, Gen2, Gen 3  
 dexosD  
 dexos is a registered trademark owned by General Motors Corp.  
**Chrysler** 500X MS-6395  
**Jaguar/Land Rover**  
 STJLR.51.5122

**Honda/Acura**  
 08798-9036  
 08798-9037  
 08798-9032  
**Mopar**  
 68152004PA  
**Mazda**  
 0000-G5-0W20-MQ  
 0000-77-0W20-QT

**Mitsubishi**  
 MZ320106  
**Nissan**  
 KLAM7-00204  
**Mercedes Benz**  
 229.61/229.71/229.72  
**Porsche**  
 C20

**Stellantis**  
 PSA B71 2010  
**Subaru**  
 SOA15208AA15A  
 SOA868V9300  
**Toyota/Lexus**  
 00279-0WQTE-01  
 00289-1QT0W  
**Volkswagen**  
 508.00/509.00

**Volvo**  
 VCC RBS0-2AE

## TYPICAL PROPERTIES:

ACEA Service Class	C2/C5/C6, A5/B5, A7/B7, A1/B1
API Service Class	SP/SN+/SN/SM
SAE Viscosity Grade (Motor Oil)	0W20
Vis @ 100°C, cSt	9.0
Vis @ 40°C, cSt	50
Viscosity Index	164
CCS Viscosity, Poise, @ °C	58@-35
Pour Point, °C	-47
Pour Point, °F	-53
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	5
HTHS Vis, cP @150°C, ASTM D4741	2.9

## PACKAGE SIZES:

11804 - 0W20 Motor Oil - quart  
 11805 - 5W20 Motor Oil - 1 gallon

## ABOUT RED LINE MOTOR OIL

- Full-synthetic ester/PAO formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance improves lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM