



RED LINE 0W30 MOTOR OIL



- For use where 5W30 is recommended, especially in colder environments
- Suitable for VW/Audi 506.10/506.00/503.01/502.00, BMW LL-01 as well as Mercedes Benz 229.5 and 229.3
- Better flow at extremely cold temperatures compared to 5W30 and 10W30

RECOMMENDED FOR:

ILSAC GF-5
API SN/SM/SL/CF
ACEA A5/B5

AC Delco 88864605

BMW LL-01 FE

GM dexos1®
dexos is a registered trademark
owned by General Motors

Mercedes Benz

MB 229.5

MB 229.3

VW/Audi

506.01

506.00

503.00

502.00-05

TYPICAL PROPERTIES:

ACEA Service Class	A5 B5
API Service Class	SN/SM/SL/SG/CF
SAE Viscosity Grade (Motor Oil)	0W30
Vis @ 100°C, cSt	11.7
Vis @ 40°C, cSt	69
Viscosity Index	166
CCS Viscosity, Poise, @ °C	59@-35
Pour Point, °C	-60
Pour Point, °F	-76
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	9
HTHS Vis, cP @150°C, ASTM D4741	3.2

PACKAGE SIZES:

- 11114 - 0W30 Motor Oil - quart
- 11115 - 0W30 Motor Oil - 1 gallon
- 11116 - 0W30 Motor Oil - 5 gallon
- 11118 - 0W30 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full-synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM