



# RED LINE 15W40 DIESEL MOTOR OIL



- Popular for Light Duty trucks including Chevrolet Duramax, Dodge Cummins and Ford Power Stroke
- Best choice in medium and heavy-duty diesel truck engines for maximum durability
- Improved drain intervals provide excellent value for commercial fleet use

## RECOMMENDED FOR:

API SN/SM/SL/SJ/SH/SG/CF/  
CK-4/CI-4/CI-4/CI-4+/CH-4  
ACEA A3/B3 E2/E5/E7/E9

### Ford

XO-15W40-5QSD  
XO-15W40-QSDW  
M2C171-C/D/E

GLOBAL DHD-1

Renault Truck RLD-3

### GM

12345634  
88862497  
88863082

### Dodge

68024966MA  
68024967MA  
68024966PB  
68024967PB

### AC Delco

19264711  
19264712  
19264713  
10-9044

### Mercedes Benz

MB 228.1  
MB 228.31

### Volkswagen

501.01  
502.00(97)

### CATERPILLAR

ECF-1-a  
ECF-3

### MTU

Type 1  
Type 2.1

### CUMMINS CES

20071  
20072  
20076  
20081

### Detroit Diesel

DDC 93K218

Deutz DQC III-05

### MACK

EO-M  
Plus  
EO-O  
Premium  
Plus

### VOLVO

VDS-2  
VDS-3  
VDS-4

## TYPICAL PROPERTIES:

ACEA Service Class	A3/B4/E5/E7/E9
API Service Class	SN/SM/CF/CK-4/CI-4/CI-4
SAE Viscosity Grade (Motor Oil)	15W40
Vis @ 100°C, cSt	14.5
Vis @ 40°C, cSt	97
Viscosity Index	155
CCS Viscosity, Poise, @ °C	65@-20
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @150°C, ASTM D4741	4.7

## PACKAGE SIZES:

- 21404 - 15W40 Diesel Motor Oil - quart
- 21405 - 15W40 Diesel Motor Oil - 1 gallon
- 21406 - 15W40 Diesel Motor Oil - 5 gallon
- 21408 - 15W40 Diesel Motor Oil - 55 gallon

## ABOUT RED LINE MOTOR OIL

- Full-synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM