

RED LINE PROFESSIONAL-SERIES 5W20 MOTOR OIL



- Full-synthetic, OEM-certified formula provides excellent low-temperature flow during cold starts
- Helps to prevent low-speed pre-ignition (LSPI) in turbocharged gas direct-injection engines
- Resistant to viscosity and thermal breakdown at high temperatures
- Developed to protect against turbocharger deposits and protects emission control system catalysts
- Can be used in vehicles powered by ethanol-containing fuels up to E85

APPROVED / CERTIFIED:

API SN Plus with Resource Conserving

ILSAC GF-5

RECOMMENDED FOR:

CHYRSLER MS-6395

FORD

WSS-M2C945-A WSS-M2C945-B1

GM

GM6094M

TYPICAL PROPERTIES:

API Service Class	SN PLUS
SAE Viscosity Grade (Motor Oil)	5W-20
Vis @ 100°C, cSt	8.4
Vis @ 40°C, cSt	45.4
Viscosity Index	164
CCS Viscosity, Poise, @ °C	36@-30
Freezing Point °C	-41
Freezing Point °F	-42
HTHS Vis, cP @150°C, ASTM D4741	2.6

PACKAGE SIZES:

12814 - 5W20 Prof-Series - quart 12815 - 5W20 Prof-Series - 5 quart 12818 - 5W20 Prof-Series - 55 gallon

ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

- FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks
- Low volatility for reduced oil consumption
- Long-life certification for reduced wear protection following factory drain intervals
- For high- and low-mileage engines
- Compatible with conventional and synthetic oils
- Withstands extreme temperatures

For health safety information, please refer to the Safety Data Sheet at REDLINEOIL.COM