



RED LINE 5W40 MOTOR OIL



- Suitable for VW/Audi 500.00/501.01/ 502.00/505.00/505.01, BMW LL-01, water-cooled Porsche A40 and Mercedes-Benz 229.1/229.3/229.5 applications
- Thicker oil film at operating temperature than a petroleum 20W50
- Popular in turbocharged applications

RECOMMENDED FOR:

API SM/SN/SL/CF
ACEA A3/B3/B4

Mercedes Benz
MB 229.1
MB 229.3
MB 229.5

BMW
07 51 0 037 633
07 51 0 038 649
81 22 9 407 547
LL-01
LL-98

VW/Audi
500.00
501.01
502.00
503.01
505.00-97
505.01-99

Lexus
08880-82790
08880-82800
Nissan
KE900-90032
KE900-90042

Mopar
05127394PB
MS-10725

TYPICAL PROPERTIES:

ACEA Service Class	A3 B3/B4
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	5W40
Vis @ 100°C, cSt	15.6
Vis @ 40°C, cSt	97
Viscosity Index	174
CCS Viscosity, Poise, @ °C	58@-30
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @150°C, ASTM D4741	4.4

PACKAGE SIZES:

- 15404 - 5W40 Motor Oil - quart
- 15405 - 5W40 Motor Oil - gallon
- 15406 - 5W40 Motor Oil - 5 gallon
- 15408 - 5W40 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM