



RED LINE 5W40 MOTOR OIL



- Suitable for VW/Audi 505.01/505.00/502.00/501.01/500.00, BMW LL-01, water-cooled Porsche A40 and Mercedes-Benz 229.5/229.3/229.1 applications
- Thicker oil film at operating temperature than a petroleum 20W50
- Popular in turbocharged applications

RECOMMENDED FOR:

API SM/SN/SL/CF	Can-Am XPS		05127394PB	PSA B71 2296
ACEA A3/B3/B4	2014-2019	Maserati (API SL/CF and ACEA A3, B3 and B4)	MS-10725	
BMW	Fiat MS-12991		MS-10850	VW/Audi
07 51 0 037 633		Mercedes Benz	MS-10896	500.00
07 51 0 038 649	Hyundai	MB 229.1	MS-12991	501.01
81 22 9 407 547		MB 229.3	Nissan	502.00-97
LL-01	Lexus	MB 229.5	KE900-90032	503.01
LL-98	08880-82790	Mopar	KE900-90042	505.00-97
	08880-82800		Porsche A40	505.01-99

TYPICAL PROPERTIES:

ACEA Service Class	A3 B3/B4
API Service Class	SN/SM/SL/CF
SAE Viscosity Grade (Motor Oil)	5W40
Vis @ 100°C, cSt	15.6
Vis @ 40°C, cSt	97
Viscosity Index	174
CCS Viscosity, Poise, @ °C	58@-30
Pour Point, °C	-45
Pour Point, °F	-49
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	6
HTHS Vis, cP @150°C, ASTM D4741	4.4

PACKAGE SIZES:

- 15404 - 5W40 Motor Oil - quart
- 15405 - 5W40 Motor Oil - 1 gallon
- 15406 - 5W40 Motor Oil - 5 gallon
- 15408 - 5W40 Motor Oil - 55 gallon

ABOUT RED LINE MOTOR OIL

- Full-synthetic ester formula for passenger cars, light trucks, performance vehicles and marine applications
- Excellent wear protection and friction reduction across a wide range of operating conditions
- High detergency allows extended drain intervals and provides increased cleanliness
- Improved fuel economy and ring seal for more power
- Superior high temperature stability and oxidation resistance increases lubrication of hot metal compared to other synthetics
- High natural viscosity index (VI) provides thicker oil film in bearings and cams
- Less evaporation than other synthetics for improved efficiency and ring seal
- All products are completely compatible with other conventional and synthetic motor oils

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM