



RED LINE 75W85 GL-5 GEAR OIL



- Popular in many late model BMW, Dodge, Focus RS, Jeep, Mercedes-Benz differentials, Toyota light truck, Lexus differentials and transfer cases
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- This product is not designed for use in most manual transmissions or transaxles with synchronizers, as extreme slipperiness may cause shifting problems
- Known formerly as LightWeight Gear Oil
- Also popular in many Formula racing transaxles, including Hewland LD-200 and FTR sequential
- Satisfies the gear oil viscosity requirements of SAE 75W80, 75, 80, and 85, as well as SAE 30 and SAE 10W30 motor oil

RECOMMENDED FOR:

API GL-5 & MT-1
MIL-L2105E
SAE J2360

TOYOTA/LEXUS GEAR OIL LT/LX
GM 88862826/SAF Carbon Mod
CHRYSLER/DODGE/JEEP 05136035AA

MB 235.15/235.7/235.74
BMW 83 12 0 445 838/BOT 448
AUDI G 052 513

TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W85
Vis @ 100°C, cSt	11.5
Vis @ 40°C, cSt	66.0
Viscosity Index	171
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	300 @ -40°C

PACKAGE SIZES:

- 50104 - 75W85 GL-5 Gear Oil - quart
- 50105 - 75W85 GL-5 Gear Oil - 1 gallon
- 50106 - 75W85 GL-5 Gear Oil - 5 gallon
- 50107 - 75W85 GL-5 Gear Oil - 16 gallon
- 50108 - 75W85 GL-5 Gear Oil - 55 gallon

ABOUT RED LINE GEAR OIL FOR DIFFERENTIALS

- Full-synthetic formulas created from polyol ester base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester base stocks and friction modifiers provide additional slipperiness to lower operating temperatures by reducing the sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetics and conventional gear oils
- Exceed API GL-5 specifications
- Engineered to provide the highest degree of protection and improvement of differential efficiency for better mileage, longer drain intervals and less wear

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM