



RED LINE 75W85 GL-5 GEAR OIL

- Popular in many late model BMW, Dodge, Focus RS, Jeep, Mercedes-Benz differentials, Toyota light truck, Lexus differentials and transfer cases, Formula racing transaxles, including Hewland LD-200 and FTR sequential
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- Not designed for use in most manual transmissions or transaxles with synchronizers, as extreme slipperiness may cause shifting problems
- Also satisfies the gear oil viscosity requirements SAE 30 and SAE 10W30 motor oil
- Full-synthetic formulas created from polyol ester base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester base stocks and friction modifiers for additional slipperiness to lower operating temperatures by reducing sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetic and conventional gear oils

RECOMMENDED FOR:

API GL-5/MT-1/MIL-L2105E
SAE J2360

Acura

Alfa Romeo

Audi

Buick

BMW/Mini

83 12 0 445 838

83 22 2 295 532

83 22 2 413 511

83 22 2 413 512

83 22 2 447 362

Castrol, BOT 448

Hypoid Axle Oil G1

Hypoid Axle Oil G2

Hypoid Axle Oil G3

Hypoid Axle Oil G4

Cadillac

Chrysler/Dodge/Jeep

05136035AA

68083381AA

68083381AA

Fiat

Ford

WSS-M2C942-A

XY-75W85-QL

Genesis

GM

19300457

88862826

92184900

SAF Carbon Mod

GMC

Honda/Acura

08200-9014A

Hypoid Gear Oil HGO-1

Hyundai

Jeep

Kia

Land Rover

Lexus

Lincoln

Maserati

Mazda

K020-01-SG1

Maserati

Mazda

K020-01-SG1

Mercedes-Benz

235.15

235.62

235.7

235.74

239.71

239.72

A 000 989 73 04

A 000 989 88 03

A 001 989 59 03

A 0012 989 33 03

A 002 989 02 03

MG

Mitsubishi

Nissan/Infinity

KDL38-75801P

Ram

Scion

Subaru

Toyota/Lexus

08885-02506

08885-02606

08885-81060

Gear Oil LT/LX

Volvo

G 052 513

VW/Audi

G 052 513

TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W85
Vis @ 100°C, cSt	11.5
Vis @ 40°C, cSt	66.0
Viscosity Index	171
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	300 @ -40°C

PACKAGE SIZES:

50104 - 75W85 GL-5 Gear Oil - quart

50105 - 75W85 GL-5 Gear Oil - 1 gallon

50106 - 75W85 GL-5 Gear Oil - 5 gallon

50107 - 75W85 GL-5 Gear Oil - 16 gallon

50108 - 75W85 GL-5 Gear Oil - 55 gallon

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM