



RED LINE 75W90 GL-5 GEAR OIL



- Most popular Red Line gear oil, with thousands of applications for passenger cars, light trucks, and racing vehicles
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- This product is not designed for use in most manual transmissions or transaxles in passenger vehicles, since the extreme slipperiness may cause synchronizer mesh issues that lead to shifting problems
- Recommended for API GL-5, GL-6, MT-1, MIL-L-2105E, SAE J2360 and Chrysler spec MS-9763
- Suitable replacement for a differential calling for 80W90 or SAE 90 gear oil.

RECOMMENDED FOR:

API GL-5 and MT-1
MIL-L-2105E
SAE J2360
Chrysler MS-9763

Castrol	M2C119-A	12345841	9986115
SAF-Carbon Mod	ESP-M2C154-A	12345977	9986207
SAF-XO	WSP-M2C197-A	12378261	9986290
SAFX-LS	WSP-M2C201-A	12378557	88900701
	WSP-M2C939-A	88862624	89021591
Ford	XY-75W90-QLS	88862625	89021671
C6AZ-19580-C	XY-75W90-TQL	88900401	89021669
ESW-M2C50-A	XY-80W90-QL	88901362	9121965
ESW-M2C57-A		89021671	93165383
ESW-M2C154-A	GM	89021675	19352759
ESW-M2C104-A	1050010	89021676	88863089
Synthetic OSP	ES-PM-M2013	1052271	89021677
SAF-XO	M2C104-A	10950849	89021678
SAFX-LS	M2C105--A	10953455	92184900

Mazda
0000-77-80W9-QT

Fuchs
Titan Race Syn 5

Nissan
KLD37-00001P

Mitsubishi
3775610
8149630
MZ320345
DiaQueen LSD Gear Oil

Subaru
SOA635001
SOA635048

Toyota
08885-81006

Mercedes Benz
235.0
235.20
235.6
235.8
A 001 989 17 03-10
A 001 989 27 03-10
A 001 989 28 03-10
A 001 989 33 03-10

TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W90
Vis @ 100°C, cSt	16.1
Vis @ 40°C, cSt	108
Viscosity Index	161
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	1100 @-40°C

PACKAGE SIZES:

- 57904 - 75W90 GL-5 Gear Oil - quart
- 57905 - 75W90 GL-5 Gear Oil - 1 gallon
- 57906 - 75W90 GL-5 Gear Oil - 5 gallon
- 57907 - 75W90 GL-5 Gear Oil - 16 gallon
- 57908 - 75W90 GL-5 Gear Oil - 55 gallon

ABOUT RED LINE GEAR OIL FOR DIFFERENTIALS

- Full-synthetic formulas created from polyol ester/PAO base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester/PAO base stocks and friction modifiers provide additional slipperiness to lower operating temperatures by reducing the sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetics and conventional gear oils
- Exceed API GL-5 specifications
- Engineered to provide the highest degree of protection and improvement of differential efficiency for better mileage, longer drain intervals, and less wear

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM