



RED LINE 75W85 GL-5 GEAR OIL

- Popular in many late model BMW, Dodge, Focus RS, Jeep, Mercedes-Benz differentials, Toyota light truck, Lexus differentials and transfer cases, Formula racing transaxles, including Hewland LD-200 and FTR sequential
- Contains additional friction modifiers for suitability with clutch-type limited slip differentials - for most LSDs, no additional friction modifiers are required
- Not designed for use in most manual transmissions or transaxles with synchronizers, as extreme slipperiness may cause shifting problems
- Also satisfies the gear oil viscosity requirements SAE 30 and SAE 10W30 motor oil
- Full-synthetic formulas created from polyol ester base stocks, offer excellent lubrication under extreme conditions
- High viscosity-index (VI) to provide relatively constant viscosity and film thickness with varying temperature change
- Ester base stocks and friction modifiers for additional slipperiness to lower operating temperatures by reducing sliding friction in hypoid gears
- Superior shear stability and reduced oxidation compared to other synthetic and conventional gear oils

RECOMMENDED FOR:

API GL-5/MT-1/MIL-L2105E
SAE J2360

Acura

Alfa Romeo

Audi

Buick

BMW/Mini

83 12 0 445 838
83 22 2 295 532
83 22 2 413 511
83 22 2 413 512
83 22 2 447 362
Castrol, BOT 448
Hypoid Axle Oil G1
Hypoid Axle Oil G2
Hypoid Axle Oil G3
Hypoid Axle Oil G4

Cadillac

Chrysler/Dodge/Jeep

MS-A0450
68083381AA
68378949AA
68237820AA
68210057AA
68218654AA
05136035AA
68232948AA
68333589AA

Fiat

Ford
WSS-M2C942-A
XY-75W85-QL

Genesis

GM
19300457
88862826
92184900
SAF Carbon Mod

GMC

Honda/Acura

08200-9014A
Hypoid Gear Oil HGO-1

Hyundai

Jeep

Kia

Land Rover

Lexus

Lincoln

Maserati

Mazda
K020-01-SG1

Mazda

K020-01-SG1

Mercedes-Benz

231.1
235.15
235.62
235.7
235.74
239.71
239.72
A 000 989 73 04
A 000 989 88 03
A 001 989 59 03
A 001 989 33 03
A 002 989 02 03

MG

**Mopar LL Hypoid
gear oil**

Mitsubishi

**Nissan/Infiniti
KDL38-75801P**

Ram

Scion

Subaru

Toyota/Lexus

08885-02506
08885-02606
08885-81060

Gear Oil LT/LX

Volvo

G 052 513

VW/Audi

G 052 513

TYPICAL PROPERTIES:

API Service Class	GL 5+
SAE Viscosity Grade (Gear Oil)	75W85
Vis @ 100°C, cSt	11.5
Vis @ 40°C, cSt	66.0
Viscosity Index	171
Pour Point, °C	-45
Pour Point, °F	-49
Brookfield Viscosity, Poise	300 @ -40°C

PACKAGE SIZES:

- 50104 - 75W85 GL-5 Gear Oil - quart
- 50105 - 75W85 GL-5 Gear Oil - 1 gallon
- 50106 - 75W85 GL-5 Gear Oil - 5 gallon
- 50107 - 75W85 GL-5 Gear Oil - 16 gallon
- 50108 - 75W85 GL-5 Gear Oil - 55 gallon

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM