



RED LINE MT-LV 70W/75W GL-4 GEAR OIL



- Recommended for Mercedes 235.10, Dodge/Fiat BOT 350 M, GM BOT 303 mod, Toyota/Scion Manual Transmissions Gear Oil LV, VW/Audi and BOT 270A Graziano Transaxle for Aston Martin, Audi & Lamborghini.
- Safe for brass synchros, as it lacks the reactive sulfurs found in most GL-5 oils that cause damage
- Offers quicker shifts, perfect synchronizer coefficient of friction
- Low fluid friction to improve power transfer
- Eliminates notchy shifting, even when cold
- High performance gear protection and longer synchro life
- Satisfies the gear oil viscosity requirements for 70W & 75W
- Recommended for GL-1, GL-3 and GL-4 applications as well as where most special synchromesh fluids are

RECOMMENDED FOR:

API GL-4/GL-3/GL-1
SAE 70W/75W

Aston Martin, Audi R8, and
Lamborghini with Graziano
transaxles
Castrol BOT 270A

BMW
X-Drive Transfer Case Fluid
83 22 0 306 816
83 22 0 397 244

Cadillac
19331044

Castrol
BOT 270A
BOT 350M3
BOT 303 mod

Chevron
GS CALTEX MTF HD 70W

Chrysler/Dodge/Jeep
9.55550-IMZ6

Dodge/Fiat
68092630AA

Ford
WSS-M2C200-D2
XT-11-QDC

GM
10-4037
19259104
19259105

Honda (Euro Market)
i-Shift MTF-3 or MTF-III

Hyundai/Kia
00232-19063

Jaguar/Land Rover
C2Z25586

MB
235.10
235.73
317
001 989 26 03 10
A 001 989 98 03 09

Nissan/Infiniti
999MP-TF0870P
TF0870

Porsche
000 043 300 36
000 043 301 36
000 043 305 63

Shell
SPIRAX S6 GHME 70W
TF 0870

SK
HK MTF 70W

Toyota
MT Gear Oil LV 75W
08885-81040

Toyota/Lexus
Genuine Transfer Case Gear Oil LF 75W
08885-81080

Toyota/Scion
Manual Transmission Oil LV
08885-81001

VW/Audi
G 052 171
G 052 512 A2
G 055 515
G 052 527 A2
G 052 725
G 052 726
G 060 726 A2
G 070 726 A2

TYPICAL PROPERTIES:

API Service Class	GL-4
SAE Viscosity Grade (Gear Oil)	70W/75W
Vis @ 100°C, cSt	6.5
Vis @ 40°C, cSt	30.6
Viscosity Index	175
Pour Point, °C	-60
Pour Point, °F	-76
Brookfield Viscosity @ -40°C, Poise	60

PACKAGE SIZES:

- 50604 - MT-LV 70W/75W GL-4 - quart
- 50605 - MT-LV 70W/75W GL-4 - 1 gallon
- 50606 - MT-LV 70W/75W GL-4 - 5 gallon
- 50607 - MT-LV 70W/75W GL-4 - 16 gallon
- 50608 - MT-LV 70W/75W GL-4 - 55 gallon

ABOUT RED LINE GEAR OIL FOR MANUAL TRANSMISSIONS

- Appropriate coefficient of friction for most manual transmission synchronizers (other synthetic gear oils are often too slippery for proper synchro engagement)
- Red Line offers lubricants to pinpoint nearly every transmission application
- MT-LV, MTL, MT-85 and MT-90 are not for use in differentials with hypoid gears
- Excellent gear and synchro protection, balanced slipperiness for easier shifting in cold climates
- Excellent for high- and low-mile transmissions
- Compatible with petroleum and other synthetics

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM